# PCR Guidance-Texts for Building-Related Products and Services

## From the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU)

## Part B: Requirements on the EPD for Solid wood products

www.ibu-epd.com

Institut Bauen und Umwelt e.V.



Imprint

Publisher

Institut Bauen und Umwelt e.V.

Hegelplatz 1
10117 Berlin

## Changelog

| Source | Date | Version | Author | Release notes |
|---|---|---|---|---|
| Template | 09.03.2023 | v1 | *Verification Agency* | Initial version |
| PCR | 20.06.2023 | v3 | *Patrick Bamou* | "factury" zu "factory" geändert. |
| PCR | 28.06.2023 | v4 | *Lucas Martin* | - |
| PCR | 28.06.2023 | v7 | *Lucas Martin* | Adjustments to table 3.1 |
| PCR | 28.06.2023 | v6 | *Lucas Martin* | Adjustments to table 3.1 |
| PCR | 28.06.2023 | v5 | *Lucas Martin* | Adjustments to table 3.1 |

© Institut Bauen und Umwelt e.V. Any type of reproduction, including excerpts thereof, is only permitted with the publisher's approval.

## Scope

This document contains the Requirements on an Environmental Product Declaration (EPD) for the range of environmental product declarations published by the Institut Bauen und Umwelt e.V. (IBU) based on the /EN 15804/ standard. The document applies for:

- Solid wood, not technically dried u > 20% (e.g. sawn wood, not technically dried, construction logs, not technically dried)
- Solid wood, technically dried u < 20%, single-part (e.g. technically dried sawn wood, rough-sawn, levelled or planed, MassivHolz MH-Plus®-Si and MH-Fix®-NSi, construction logs, boards, plywood, window scantling, solid wood parquet, mosaic parquet)
- Solid wood, technically dried u < 20%, multiple parts, joined longitudinally (e.g. single-part finger-jointed softwood, structural timber, KVH®)
- Solid wood, technically dried u < 20%, multiple parts, joined longitudinally and glued in several layers (e.g. glued laminated timber, Duo-Balken® and Trio-Balken® (laminated beams), board stack elements – wall plug elements, veneer laminates-S)
- Solid wood, technically dried u < 20%, multiple parts, joined longitudinally and glued cross-wise (e.g. cross-laminated timber, veneer laminates-Q, multiple-layer parquet made from solid wood).

These products comprise single or multiple solid wood components from forest timber generated by sawing, chipping or cutting longitudinally. Exceptions involve products made from chips, wood fibres or other mini wood particles. The solid wood components can be glued together.
The requirements on the EPD include:

- Requirements on the /EN 15804/ standard as a European core EPD
- Complementary requirements on IBU EPD

The calculation rules for the life cycle assessment and requirements on the project report are specified in a separate document as Part A of the Product Category Rules.
The general principles for the EPD range of Institut Bauen und Umwelt e.V. (IBU) also apply.

## Hints for using the database system

**Insert text:** Requirements on the content are shown in blue colour under the respective titles. These coloured texts can be edited by clicking. In the appearing text editor, the requirements on the content are outlined above for further assistance. The relevant text can be entered below. After confirming the input, texts are incorporated into the document and displayed.

**Inserting images:** Using the text editor, "broad" and "small" pictures can be added. If you click on the respective button in the editor, you can select the image file and upload it. After uploading, the figure is shown in the text editor and can be changed in size by clicking and pulling the edges.

**Technical tables:** Click on the table, to open the table editor. Insert your values (= numbers) in the respective field in the column "Value". For each row, you can choose between 3 value types: value (= number), range (= consisting of two numbers separated with a hyphen) and a free text (e.g. “test passed after 3 days”). On the far left, you can hide rows that are not relevant by clicking on the check. Click the button “add new property” to generate a new row with free text space. It is not allowed to insert a picture instead of a table!

**Chapter 5, "Results of the LCA":** Click on the first table "system boundaries" and select all life stages you want to declare in the following dialogue. Then the following three tables are adjusted according to your entries. Now you can insert numerical values by clicking on the tables. The numerical values are to be indicated with three significant digits. To achieve an optimal representation, the "exponential view" can be selected for each impact indicator.

**Storing/saving** is done fully automatically.

**The first three pages** of the document will be deleted automatically after creation of the EPD.

**Labelled sample texts** are proposals to facilitate the creation of an EPD. If they are accepted into an EPD, they should be checked for their accuracy and if necessary adapted for the specific product.

Requirements on content and format:

**The chapters of the EPDs** must be described in a compact form and in a factually and technically correct way. Judgmental, comparative, or promotional texts are not permitted unless specifically requested in the PCR or if necessary in the context of the EPD. Each document is carefully checked before publication.

**(The) extent of an EPD:** For technical reasons, an EPD may contain one data set only. This means that the tables for the LCA results are available only once per EPD. All four tables of the LCA results (Chapter 5) must be located entirely on one side.

**Quotations** should be indicated in italic (formatting), for example: EN 15804. The literature cited is to be shown completely in the references (Chapter 8).

## Product-group-specific LCA calculation rules from PCR part A

**"Solid wood products:**

Regarding glues, either the mix of glue
systems available on the market (average glues) or specific data can be used
for the LCA. The approach selected shall be documented. In the case of
non-glued bonds, the binding method shall be declared in the EPD.

The resource aspect of wood shall be
calculated taking into account the inherent characteris-tics of the material.
CO2 fixation is calculated as a resource taken from the atmosphere.

The lower calorific value of absolutely dry
wood is applied for the calculation of the indicator “use of renewable
secondary fuels”.

# ENVIRONMENTAL-PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

| | |
|---|---|
| Owner of the Declaration | |
| Publisher | Institut Bauen und Umwelt e.V. (IBU) |
| Programme holder | Institut Bauen und Umwelt e.V. (IBU) |
| Declaration number | |
| Issue date | |
| Valid to | |

**Name of declared product**

## Name of manufacturer/association


www.ibu-epd.com | https://epd-online.com

# Large picture of the product

**Maximum file size: 4 MB**

**Recommended picture size: width 1500 pixel, height 1000 pixel**

**Insert the picture:** Click on "Images and Logos" in the tree view and specify the location of the image on your PC in the dialog on the right.



LOGO

# 1. General Information

## Name of the manufacturer

**Programme holder**

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

**Declaration number**

**This declaration is based on the product category rules:**

Name of PCR, 08.2021
(PCR checked and approved by the SVR)

**Issue date**

**Valid to**

[Unterschrift]

Dipl.-Ing Hans Peters
(chairman of Institut Bauen und Umwelt e.V.)

[Unterschrift]

Dr. Alexander Röder
(Managing Director Institut Bauen und Umwelt e.V.)

## Name of the product

**Owner of the declaration**

Name of the manufacturer
Street
ZipCode/City
Country

**Declared product / declared unit**

Name of declared product / declared unit

**Scope:**

The products, plants and their locations must be outlined, on which data the Life Cycle Assessment is based and for which the declaration applies.

For average EPDs, e.g. association EPDs, the plants/companies under review on whose data the LCA is based must be named; as an alternative, the representatively of the declaration can be depicted, e.g. for the association, by declaring the production volume covered by the LCA as a percentage of the entire volume of the declared product manufactured by all association members in the year of reference. It shall be clearly mentioned in this clause if the EPD represents an average EPD, e.g. as an association EPD.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804 bezeichnet*.

**Verification**

| |
|---|
| The standard EN 15804 serves as the core PCR |
| Independent verification of the declaration and data according to ISO 14025:2011 |
| ☐ internally ☒ externally |

[Unterschrift]

Name of verifier ,
(Independent verifier)

# 2. Product

## 2.1 Product description/Product definition

The declared products must be described.

In addition to a general product description, the trade names of the products/product groups (including any product codes) must be mentioned to which the EPD applies.

If the declaration of trade names is not meaningfully possible (e.g. in the context of association EPDs), the product description must clearly demarcate the products product groups to which the EPD applies.

Please select one of the following options and delete the header of the selected [alternative]:

**[Alternative 1a: Product according to the CPR based on a hEN]:**

For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration EN xyz:date, title and the CE-marking.

For the application and use the respective national provisions apply.

**[Alternative 1b: Products according to the CPR based on an ETA]:**

For the placing of the product on the market in the European Union/European Free Trade Association /EU/EFTA) (with the exception of Switzerland) the Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration ETA no. xyz:date, title and the CE-marking.

For the application and use the respective national provisions apply.

**[Alternative 2a: Product not harmonised in accordance with the CPR but in accordance with other provisions for harmonisation of the EU]:**

For the placing on the market in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) the following legal provisions apply:

- *Directive no. xyz: date, title*
- *Regulation no. xyz: date, title*
- and the harmonised standards based on these provisions:
- *EN xyz: date, title*

The CE-marking takes into account the proof of conformity with the respective harmonized standards based on the legal provisions above.

For the application and use the respective national provisions apply.

**[Alternative 2b: Product harmonized as well in accordance with the CPR as with other provisions for harmonisation of the EU]:**

For the placing of the product on the market in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) the Regulation (EU) No. 305/2011/ (CPR) and the following other provisions for harmonisation apply:

- *Directive (EU) xyz: date, title*
- *Regulation (EU) no. xyz: date, title*

The product needs a declaration of performance in accordance with the CPR taking into consideration /EN xyz: date/, title or /ETA no. xyz/:date, title respectively and the CE-marking.

The CE-marking for the product takes into account the Declaration of Performance in accordance with the CPR and the proof of conformity with the following harmonised standards or based on the other provisions for harmonisation:

- *EN xyz: date, title*
- *Source, date, title*

For the application and use the respective national provisions apply.

**[Alternative 3: Product for which no legal provisions for harmonisation of the EU exist]:**

For the use and application of the product the respective national provisions at the place of use apply, in Germany for example the building codes of the federal states and the corresponding national specifications.

## 2.2 Application

The designated application must be specified for the products covered in the EPD.

## 2.3 Technical Data

The technical specifications of the products within the scope of the EPD shall be listed, including the reference to the test methods/test standards for each specification.

For products with CE marking, the technical specifications must be specified in accordance with information in the declaration of performance. The properties relevant to the product should be specified in the table below. If no information is given for properties, an explanation must be given in the background report to the EPD as to why the property is not relevant to the product.

**Constructional data**

| Name | Value | Unit |
|---|---|---|
| Wood types by trade names acc. to EN 1912 | | - |
| Wood moisture acc. to EN 13183-1 | | % |
| Use of wood preservatives (the wood preservative test mark to DIN 68800-3 must be indicated) | | - |
| Compressive strength parallel acc. to EN 1995 | | $N/mm^2$ |
| Compressive strength rectangular acc. to EN 1995 | | $N/mm^2$ |
| Tensile strength parallel acc. to EN 1995 | | $N/mm^2$ |
| Tensile strength rectangular acc. to EN 1995 | | $N/mm^2$ |
| Modulus of elasticity acc. to EN 1995 | | $N/mm^2$ |
| Shear strength acc. to EN 1995 | | $N/mm^2$ |
| Shear modulus acc. to EN 1995 | | $N/mm^2$ |
| Dimensional deviation | | mm |
| Length (min. - max.) | | m |
| Width (min. - max.) | | m |
| Height (min. - max.) | | m |
| Gross density supporting components in accordance with EN 338 or DIN 1052. Non-supporting components are classified as per DIN 68364 | | $kg/m^3$ |
| Surface quality (Possible characteristic features must be indicated) | | - |
| Risk class acc. to 68800-3 | | - |
| Thermal conductivity acc. to EN 12664 | | W/(mK) |
| Specific heat capacity acc. to EN 12664 | | kJ/kgK |
| Calculation value for thermal conductivity | | W/(mK) |
| Water vapor diffusion equivalent air layer thickness acc. to EN ISO 12572 | | m |
| Water vapour diffusion resistance factor acc. to EN ISO 12572 | | - |
| Formaldehyde emissions acc. to EN 717-1 | | $\mu g/m^3$ |

Please select one of the following options and delete the header of the selected [alternative]:

**[Alternative 1a: Product according to the CPR, based on a hEN]:**

- Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *EN xyz:date, title*.
- Voluntary data: *source, date, title* (not part of CE-marking).

**[Alternative 1b: Product according to the CPR, based on an ETA]:**

- Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *ETA no. xyz, date, title*.
- Voluntary data: *source, date, title* (not part of CE-marking).

**[Alternative 2a: Product not harmonised in accordance with the CPR but in accordance with other provisions for harmonisation of the EU]:**

Performance data of the product according to the harmonised standards, based on provisions for harmonization.

Voluntary data: *source, date, title* (not part of CE-marking).

**[Alternative 2b: Product harmonized as well in accordance with the CPR as with other legal provisions of the EU]:**

- Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *EN xyz: date, title* or *ETA no. xyz, date, title* respectively.
- Performance data of the product, based on the harmonised standards, in accordance with the other provisions for harmonization.
- Voluntary data: *source, date, title* (not part of CE-marking)

**[Alternative 3: Product for which no legal provisions for harmonisation of the EU exist]:**

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision (no CE-marking).

### 2.4 Delivery status

The dimensions/quantities must be declared for the products covered in this EPD in their delivery status.

### 2.5 Base materials/Ancillary materials

The main constituents of the product or its components shall be indicated as mass percentages to enable the user of the EPD to understand the composition of the product in delivery status. This information should support safety and efficiency during installation, use, and disposal of the product.

When substances from the “Candidate List of Substances of Very High Concern for Authorisation” (SVHC) are part of the formulation with a mass percentage of > 0,1 of the mass of the construction product, i.e. when they were added to the formulation on purpose, then the substances shall be declared including CAS-number.

If the construction product is a substance or mixture under the chemical law (*REACH*), the concentration limit value refers to the entire product; if it is an article, the partial product or component applies as a unit of reference.

The Candidate list can be found on the ECHA website address: echa.europa.eu/de/home

This declaration is mandatory for all EPDs and must be formulated as follows:

1) “This product/article/at least one partial article contains substances listed in the candidate list (date: dd.mm.yyyy) exceeding 0.1 percentage by mass: yes/no”.

[if yes: List of respective SVHC and their CAS-number]

[If yes:] - Information on the concentration and/or concentration range (comparable information on hazardous properties and if relevant, information on the partial article in the case of articles)

If the construction product is a substance or mixture under the chemical law (REACH), the safety data sheet shall be made available in the EPD, e.g. by a link. In addition, the concentrations of the hazardous substance as well as its hazardous properties have to be stated in the EPD.

CMR substances in categories 1A and 1B must also be declared including CAS-number if a European harmonised classification is available as well as information on treatment with biocides. For IBU-EPDs statement 2) and 3) are mandatory.
This statement on other CMR substances which are not listed as SVHC and on biocides must be formulated as follows:

2) “This product/article/at least one partial article contains other CMR substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass: yes/no”

[If yes:] – List the concentration and/or concentration ranges (comparable to the information on a safety data sheet), provide information on hazardous properties and if relevant information on the partial article in the case of articles.

3) “Biocide products were added to this construction product or it has been treated with biocide products (this then concerns a treated product as defined by the (EU) Ordinance on Biocide Products No. 528/2012): yes/no”

[If yes:] - List the biocides referred to above.
The active substance and the product type (in-can preservative, film preservative, wood protection, etc. according to the Ordinance on Biocide Products (see also 1.4) must be indicated.

Ancillary materials and additives remaining on the product must also be declared.
If additives such as fire retardants, softeners or biocides are used, their functional chemical group must be indicated.

Especially surface coatings and hydrophobic agents.
Statements like “…free of ….” and/or “…does not contain…” may not be used.

Especially flame retardants, wood preservatives, transport protection coatings.

### 2.6 Manufacture

The manufacturing process must be described and can be illustrated using a simple graphic. If the EPD applies for several locations, the production processes must be described for all sites in case they differ.

Quality management systems can be referred to.

### 2.7 Environment and health during manufacturing

Presentation of measures relating to health protection during the manufacturing process extending beyond national guidelines (of the production country).

Presentation of measures relating to environmental protection during the manufacturing process extending beyond national guidelines or plant-specific requirements, e.g. description of special environmentally-friendly dealings with waste air, waste water, and waste as well as noise emissions.

Information on the Environment Management System or similar (if available)

### 2.8 Product processing/Installation

Description of the type of processing, machinery and tools used, dust extraction etc., auxiliary materials needed for installation as well as measures for noise reduction.
Information on the rules of technology as well as on workers safety and environmental protection is possible.

### 2.9 Packaging

Information on product-specific packaging:
type, composition, and possible reuse, recycling, energy recovery, and disposal of packaging materials (paper, pallets, foils, etc.).

### 2.10 Condition of use

Information should be provided here regarding changes in material composition over the service life of the product and/or regarding environmentally relevant material inherent properties over the service life of the product.

### 2.11 Environment and health during use

Information on the relationships between the product, the environment and health.

Information on the possible content of harmful substances or emissions.

Note: recommendations concerning cleaning, maintenance, etc. for the declared product should be listed in the corresponding section in 4 “Technical information on scenarios”.

### 2.12 Reference service life

The declaration of the reference service life (RSL) is imperative for EPDs covering the complete use stage (modules B1-B7), or if a use stage scenario is described, which refers to the lifetime of the product. If not all modules of the use stage are declared and no use stage scenario covering the full lifetime of the product is described, then the indication of the RSL (according to *ISO 15686:1, -2, -7 and -8*) is voluntary.

Information on the product’s RSL requires specification of compatible scenarios for the product stage, construction process stage and use stage. The RSL is dependent on the properties of the prod¬uct and reference in-use conditions. These conditions shall be declared together with the RSL in clause 4 and it shall be stated that the RSL applies for the reference conditions only.

If a reference service life (RSL) cannot be declared according to ISO 15686 (or it is not relevant for consideration of the LCA), this has to be stated clearly in the EPD.

In such cases, a service life can be declared in ac-cordance with the BBSR table "Service lives of components for life cycle assessment according to
BNB" (www.nachhaltigesbauen.de/baustoff-und-gebaeudedaten/nutzungsdauern-von-bauteilen.html).

It shall be unambiguously stated that a service life (not: a reference service life) in accordance with the BBSR table (or based on a manufacturer’s declaration (see below)) is not a RSL according to ISO 15686.

A service life provided by the manufacturer can be declared as an alternative to the value from the BBSR table. This information shall be accompanied by explanations on the origin of the declared service life, e.g. referring to simulations, tests, an assessment of the man¬ufacturer or statistical data, etc. and shall contain the specification of the application for which the stated service life is valid (to be provided in clause 4).

The requisite information for technical building installations should be taken from *VDI 20673*.

Description of the influences on the ageing of the product when applied in accordance with the rules of technology.

### 2.13 Extraordinary effects

**Fire**

Information on the fire performance according to *EN 13501:1* or established national standards. According to *EN 13501:1*:

- The classes of building products regarding their fire performance are predefined as: A1, A2, B, C, D, E, and F;
- The classes of flaming droplets/particles are pre-defined as: d0, d1, or d2;
- The classes for smoke density are pre-defined as: s1, s2, or s3

**Fire protection**

| Name | Value |
|---|---|
| Building material class | |
| Burning droplets | |
| Smoke gas development | |

**Water**
Information on the product performance including possible impacts on the environment following the unforeseeable influence of water, e.g. flooding.

**Mechanical destruction**
If relevant: information on the product performance including possible impacts on the environment following unforeseeable mechanical destruction.

### 2.14 Re-use phase
The possibilities of re-use, recycling, and energy recovery must be described.

### 2.15 Disposal
The possible disposal channels must be indicated.
The waste code in accordance with the European Waste Index must be described.

### 2.16 Further information
Possible sources of additional information, e.g. website, a reference source for safety data sheet.

## 3. LCA: Calculation rules

### 3.1 Declared Unit
The declared unit and the mass reference must be indicated in the appropriate table as declared. If there are several units to choose from, a suitable one must be selected. If averages are declared across various products, the average breakdown must be explained.

The declared unit is 1 m³. 1 m² can be declared as an alternative for cylindrical materials. The moisture level on delivery must be indicated,
whereby the combination of adhesives available on the market (for groups EPD) or specific data can be used for calculating glued products. The approach selected must be documented. The type of bond must be declared in the case of non-glued compounds. The ground reference must be indicated.

**Declared unit**

| Name | Value | Unit |
|---|---|---|
| Declared unit | | $m^3$ |
| Gross density | | $kg/m^3$ |
| Declared unit | | $m^2$ |
| Grammage | | $kg/m^2$ |
| Wood moisture bei Auslieferung | | % |
| Layer thickness | | m |

For IBU core EPDs (where clause 3.6 is part of the EPD): for average EPDs, an estimate of the robustness of the LCA values must be made, e.g. concerning variability of the production process, geographical representativeness and the influence of background data and preliminary products compared to the environmental impacts caused by actual production.

### 3.2 System boundary
Type of the EPD: choose as appropriate: cradle to gate, cradle to gate - with options, cradle to grave.

The modules considered in the life cycle assessment as per “system boundaries” outlined in section 5.5. of the PCR, Part A: “Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report” must be described in brief. The description should be product specific; it should be apparent as to what processes are considered in what modules.
If green electricity has been calculated, the following sentence must be declared in the IBU EPD under the assumptions:
For the environmental impact, the use of green electricity was calculated taking into account the residual electricity mix for the remaining electricity. The proportion of the electricity demand covered by green electricity in the total electricity demand is x %.

### 3.3 Estimates and assumptions
Key assumptions and estimates for interpretation of the life cycle assessment should be listed here, provided that they are not dealt with in other sections of the main clause 3 “LCA: Calculation rules”.

### 3.4 Cut-off criteria
The use of cut-off criteria as per the PCR, Part A: “Calculation Rules for the Life Cycle Assessment and Requirements on the project report” must be documented here.

### 3.5 Background data
The sources for background data in the LCA used must be provided.

### 3.6 Data quality
An estimate should be made as regards data quality (addressing both foreground and background data), whereby the age of background data used must be indicated.

For average EPDs, an estimate of the robustness of the LCA values must be made, e.g. concerning variability of the production process, geographical representatively and the influence of background data and preliminary products compared to the environmental impacts caused by the actual production.

### 3.7 Period under review
The period under review for the collection of production data and the resulting averages (if applicable) shall be documented.

### 3.8 Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product´s lifespan:

### 3.9 Allocation

The allocations of relevance for calculation (appropriation of expenses across various products) must be indicated, at least:

- Allocation of energy, auxiliary and operating materials used for individual products in a factory;
- Allocation of co-production processes;
- Allocation in the use of recycled and/or secondary raw materials;
- Loads and benefits beyond the system boundary from recycling or energy recovery of packaging materials and production waste;
- Loads and benefits beyond the system boundary from recycling or energy recovery from the end of life of the product.
- Allocations in the forestry chain,
- Allocations in the saw mill,
- Allocation of energy, auxiliaries and consumables used in the saw mill or board factory.
- When using waste wood or recycled wood fibres, e.g. for energy recovery: Balancing the bound CO2 and energy content (Hu).

whereby reference must be made to the modules in which the allocations are performed.

### 3.10 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.
The used background database has to be mentioned.

## 4. LCA: Scenarios and additional technical information

**Characteristic product properties**
**Information on biogenic carbon**

The biogenic carbon content quantifies the amount of biogenic carbon in a construction product leaving the factory gate, and it shall be separately declared for the product and for any accompanying packaging.
If the total mass of biogenic carbon containing materials is less than 5 % of the total mass of the product and accompanying packaging, the declaration of biogenic carbon content may be omitted. The mass of packaging containing biogenic carbon shall always be declared.

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO2.

**Information on describing the biogenic carbon content at factury gate**

| Name | Value | Unit |
|---|---|---|
| Biogenic carbon content in product | | kg C |
| Biogenic carbon content in accompanying packaging | | kg C |

The following technical scenario information is required for the declared modules and optional for non-declared modules. Modules for which no information is declared can be deleted; additional information can also be listed if necessary.

The following technical information is a basis for the declared modules or can be used for developing specific scenarios in the context of a building assessment if modules are not declared (MND).

A5 is not declared including the disposal of the packaging material on the construction site, the amounts of packaging materials included in the LCA calculations must be declared as technical scenario information for Module A5.

**Transport to the building site (A4)**

| Name | Value | Unit |
|---|---|---|
| Litres of fuel | | l/100km |
| Transport distance | | km |
| Capacity utilisation (including empty runs) | | % |
| Gross density of products transported | | kg/m$^3$ |
| Capacity utilisation volume factor | | - |

**Installation into the building (A5)**

| Name | Value | Unit |
|---|---|---|
| Auxiliary | | kg |
| Water consumption | | m$^3$ |
| Other resources | | kg |
| Electricity consumption | | kWh |
| Other energy carriers | | MJ |
| Material loss | | kg |
| Output substances following waste treatment on site | | kg |
| Dust in the air | | kg |
| VOC in the air | | kg |

**Use or application of the installed product (B1) see section 2.12 "Use"**

| Name | Value | Unit |
|---|---|---|

**Maintenance (B2)**

| Name | Value | Unit |
|---|---|---|
| Information on maintenance | | - |
| Maintenance cycle | | Number/RSL |
| Water consumption | | m$^3$ |
| Auxiliary | | kg |
| Other resources | | kg |
| Electricity consumption | | kWh |
| Other energy carriers | | MJ |
| Material loss | | kg |

**Repair (B3)**

| Name | Value | Unit |
|---|---|---|
| Information on the repair process | | - |
| Information on the inspection process | | - |
| Repair cycle | | Number/RSL |
| Water consumption | | $m^3$ |
| Auxiliary | | kg |
| Other resources | | kg |
| Electricity consumption | | kWh |
| Other energy carriers | | MJ |
| Material loss | | kg |

**Replacement (B4) / Refurbishment (B5)**

| Name | Value | Unit |
|---|---|---|
| Replacement cycle | | Number/RSL |
| Electricity consumption | | kWh |
| Litres of fuel | | l/100km |
| Replacement of worn parts | | kg |

In case a **reference service life** according to applicable ISO standards is declared then the assumptions and in-use conditions underlying the determined RSL shall be declared. In addition, it shall be stated that the RSL applies for the reference conditions only.

The same holds for a service life declared by the manufacturer. Corresponding information related to in-use conditions needs not be provided if a service life taken from the list on service life by BNB is declared.

**Reference service life**

| Name | Value | Unit |
|---|---|---|
| Reference service life (according to ISO 15686-1, -2, -7 and -8) | | a |
| Life Span (according to BBSR) | | a |
| Life Span according to the manufacturer | | a |
| Declared product properties (at the gate) and finishes | | - |
| Design application parameters (if instructed by the manufacturer), including the references to the appropriate practices and application codes | | - |
| An assumed quality of work, when installed in accordance with the manufacturer's instructions | | - |
| Outdoor environment, (for outdoor applications), e.g. weathering, pollutants, UV and wind exposure, building orientation, shading, temperature | | - |
| Indoor environment (for indoor applications), e.g. temperature, moisture, chemical exposure | | - |
| Usage conditions, e.g. frequency of use, mechanical exposure | | - |
| Maintenance e.g. required frequency, type and quality and replacement of components | | - |

**Operational energy use (B6) and Operational water use (B7)**

| Name | Value | Unit |
|---|---|---|
| Water consumption | | $m^3$ |
| Electricity consumption | | kWh |
| Other energy carriers | | MJ |
| Equipment output | | kW |

**End of life (C1-C4)**

| Name | Value | Unit |
|---|---|---|
| Collected separately waste type waste type | | kg |
| Collected as mixed construction waste | | kg |
| Reuse | | kg |
| Recycling | | kg |
| Energy recovery | | kg |
| Landfilling | | kg |

**Reuse, recovery and/or recycling potentials (D), relevant scenario information**

| Name | Value | Unit |
|---|---|---|

## 5. LCA: Results

In Table 1 "Description of the system boundary", all declared modules shall be indicated with an "X"; all modules that are not declared shall be indicated with "MND" (As default the modules B3, B4, B5 are marked as MNR – module not relevant). In the following tables, columns can be deleted for modules that are not declared. Indicator values should be declared with three valid digits (eventually using exponential form (e.g. 1,23E-5 = 0,0000123). A uniform format should be used for all values of one indicator.
If several modules are not declared and therefore have been deleted from the table, the abbreviations for the indicators can be replaced by the complete names, while the readability and clear arrangement should be maintained; the legends can then be deleted.
If due to relevant data gaps, an indicator cannot be declared in a robust way, then the abbreviation “IND” (indicator not declared) should be used for this indicator.

- 0 - calculated value is 0
- 0 - value falls under the cut-off
- 0 - assumption which exclude any flows (e.g. exported electricity A1-A3)
- IND – in cases where the inventory does not support the methodological approach or the calculation of the specific indicator IND shall be used.

If no reference service life is declared (see chapter 2.13 "Reference Service Life"), the LCA results of the modules B1-B2 and B6-B7 shall refer to a period of one year. This shall then be indicated as an explanatory text below the tables. In addition, the formula for the quantification of such B-modules over the total life cycle shall be provided.

**DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)**

| PRODUCT STAGE | | | CONSTRUCTION PROCESS STAGE | | USE STAGE | | | | | | | END OF LIFE STAGE | | | | BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Raw material supply | Transport | Manufacturing | Transport from the gate to the site | Assembly | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| **A1** | **A2** | **A3** | **A4** | **A5** | **B1** | **B2** | **B3** | **B4** | **B5** | **B6** | **B7** | **C1** | **C2** | **C3** | **C4** | **D** |

**RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: [declared unit and product]**

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

**RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: [declared unit and product]**

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

**RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: [declared unit and product]**

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: [declared unit and product]**

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these

results are high or as there is limited experienced with the indicator.

## 6. LCA: Interpretation

To facilitate comprehension of the life cycle assessment, both the relevant indicators of the life cycle inventory and the indicators of the impact assessment declared in section 5 “LCA results” have to be interpreted in a dominance analysis. An illustration of the results with figures is recommended, e.g. for the dominance analysis, the distribution of impacts across the modules, the CO2-balance, etc. as appropriate for a reader to understand the environmental profile of the declared product. The interpretation shall also include a description of the time frame and/or variability of the LCIA results (in qualitative or quantitative terms) if the EPD is valid for several products or producers.

## 7. Requisite evidence

As a general rule, all statements must be documented with measured data (presented by the corresponding test certificates). The methods of evidence and the test conditions have to be described together with the results.

If substances are not detected, the limit of detection must be included in the declaration.

Interpreting statements such as “… free of …” or “… are entirely harmless …” are not allowed.

If evidence required by the specific PCR part B is not provided, this has to be justified under the respective title for the required evidence.

If relevant for the scope of application of the declared product, or if derivable from its material composition, it is recommended to provide additional adequate evidence.

7.1 Formaldehyde
When using adhesives containing formaldehyde, subsequent formaldehyde emissions must be evaluated by testing to EN 717-1.
The measuring procedure must be indicated. 7.2 MDIWhen using adhesives based on polymer MDI, the products must be examined in accordance with NIOSH (National Institute for Occupational Safety and Health) Physical and Chemical Analytical Method 142 (P&CAM142) or BIA 7670 or RAL UZ-76. The measuring procedure must be indicated. Note: These methods are analysed identically. It is not necessary to provide information on the compulsory detection of MDI in the case of cold-bonded load-bearing solid wood products containing moisture-cured one-component polyurethane adhesives. 7.3 Fire gas toxicityMeasurement to DIN 53436
Optional info; this measurement is specified for wooden composites used in public venues.
Note: DIN 53436 is the test standard referred to in DIN 4102-1. Accordingly, PCR-conformant testing can be assumed when indicating DIN 4102-1. 7.4 VOC emissions
Optional for products which are exclusively used in outdoor applications.
Test procedure in line with the AgBB diagram indicating the measuring agency, date and results as a range of values. At least the following must be declared (VOC verification is optional if the EPD is valid for a shorter period of time (1 year)):

**AgBB overview of results (28 days [µg/m³])**

| Name | Value | Unit |
|---|---|---|
| TVOC (C6 - C16) | | µg/m³ |
| Sum SVOC (C16 - C22) | | µg/m³ |
| R (dimensionless) | | - |
| VOC without NIK | | µg/m³ |
| Carcinogenic Substances | | µg/m³ |

**AgBB overview of results (3 days [µg/m³])**

| Name | Value | Unit |
|---|---|---|
| TVOC (C6 - C16) | | µg/m³ |
| Sum SVOC (C16 - C22) | | µg/m³ |
| R (dimensionless) | | - |
| VOC without NIK | | µg/m³ |
| Carcinogenic Substances | | µg/m³ |

## 8. References

**Standards**

**EN 15804**

EN 15804:2012+A1 2013, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

**EN 15804**

EN 15804:2012+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

**ISO 14025**

EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

**Further References**

**Title of the software/database**

Title of the software/database. Addition to the title, version. Place: Publisher, Date of publication [Access on access date].

**IBU 2021**

Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V., Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021
www.ibu-epd.com

The literature referred to in the Environmental Product Declaration must be listed in full.Standards already fully quoted in the EPD do not need to be listed here again.
The current version of PCR Part A and PCR Part B of the PCR document on which they are based must be referenced.

LOGO


**Publisher**

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



**Programme holder**

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com


**Author of the Life Cycle Assessment**

**Owner of the Declaration**